





FEATURES

- 50°C temperature rating
- ComApMRS11controller
- Enclosed Silenced Canopy
- Powder coated finish
- Fork Points and centre liftinglug
- ABB Breakers
- 110% double bunded base
- Emergency E stop
- Australian Compliant Wiring and M.E.N link
- Remote Start and ATSfeature
- Site safe lockable canopy
 Pricing includes commissio
- Pricing includes commissioning and pre delivery run in

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010

OPTIONAL UPGRADES

Fire extinguisher battery & starter Isolator Solar battery charger 3-way fuel valve ComAp cell phone monitoring

WARRANTY

2 year - 1000 hour

Prime power (prp) Prime power is available for an unlimited number of annual hours invariable load application, in accordance with gb/t2820-97 eqv iso8528; a 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby power rating (esp) The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

GEN 22FT

Silent Diesel Generator

ENGINE DATA

Make & Model	FAW 4DW91-29D	
Туре	Water Cooled, Nature Aspirate Engine	
Output Rating	Ps/Rpm	25.8/1500
	Kw/Min	21/1500
Bore X Stroke	Mm	114X 135mm
Position Displacement	L	2.54
Fuel Type	Diesel	
Fuel Consumption (Based On 75% Full Load)	L/H	4.1
Lube Oil Pump Capacity	L	8
Coolant Capacity	L	16
Battery X Quantity	1 X 80Ah	
Fuel Tank Capacity	L	145

ALTERNATOR DATA

Alternator	DINGOL DG184ES	
Frequency	(Hz)	50
Output Rating	Continuous (KVA)	20
	Standby (KVA)	22
No. of Phase		3 Phase, 4 Wire
Rated Voltage	V	240/415
Power Factor		0.8 (Lagging)
Voltage Regulation	%	+-1
Excitation	Self Exciting	
Insulation	Class H	

SOUND

Sound Level	7m dB(A)	63

DIMENSIONS

Dimensions	Length (mm)	2000
	Width (mm)	900
	Height (mm)	1190
Dry weight	Kg	950