Mine Spec LED mobile

Model: ENV6MYMOBILE



EnviroLED

Lighting Towers

Highly efficient Minespec 6 X 320W Multi LED delivering super bright light visibility and significant fuel savings

EnviroLED

Lighting Towers

Mine Spec LED Moor

KEY FEATURES







· Massive 249300 Lumen



· 7800 M2 @ 20 Lux



· Easy to use Deep Sea L401 MKII Controller



Hydraulic Tilting Head



Extendable Draw Bar



 Super Fuel Efficient Japanese Yanmar engine with 200 Hour Run Time



Italian made for tough Australian conditions, delivering super bright light for continuous night work in mining, construction and civil works.







Lighting Towers Technical Specifications

Rated Power Rated Power 3.5 kW Operating temperature 3.5 kW Operating temperature 3.5 kW Control unit Deep Sea L401 MKII Engine Yanmar 3TNV68 Speed 1500 rpm Coolant Liquid Cylinders Emissions Stage V Alternator Alternator Rated outlet 3.5 kVA Regulation Brushless Voltage accurancy 4-/- 5% Auxillary power 1.2 kVA Fuel Consumption Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road-towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm	Performance data	
Operating temperature Sound level Gound level Goolant Coolant Liquid Cylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kWA Regulation Brushless Voltage accurancy 4/- 5% Auxillary power 1.2kVA Fuel Consumption O,60 I/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height Lifting system Hydraulic Rotation Station Stage W Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Optional not included: Brushless Shipment Dimension 235x147x240 cm Weight Truck 10 Coolant Vanner 3TNV68 Sage L401 MKII Engine Yanner 3TNV68 Stabilizers Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Dimension 235x147x240 cm	Rated frequency / voltage	50 Hz / 230 V
Sound level 61 dB @ 7 m Control unit Deep Sea L401 MKII Engine Yanmar 3TNV68 Speed 1500 rpm Coolant Coylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy 4/- 5% Auxillary power 1.2kVA Fuel Consumption 0,60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Rated Power	3.5 kW
Control unit Engine Yannar 3TNV68 Speed 1500 rpm Coolant Liquid Cylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy 4/- 5% Auxillary power 1.2kVA Fuel Consumption 7 Joes Ling Alumen Rank 120L Fuel Diesel Running time 200 Hr Galvanized mast height Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional not included: Weekly timer Hydraulic resistance Shipment Dimension 235x147x240 cm Weight Truck 100 Pool kg Truck 100 Liquid 1500 rpm Li	Operating temperature	-30/+50°C
Engine Yanmar 3TNV68 Speed 1500 rpm Coolant Liquid Cylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy +/-5% Auxillary power 1.2kVA Fuel Consumption 0,601/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Sound level	61 dB @ 7 m
Speed1500 rpmCoolantLiquidCylinders3EmissionsStage VAlternatorLinz AlumenRated outlet3.5kVARegulationBrushlessVoltage accurancy4/- 5%Auxillary power1.2kVAFuel Consumption0,60 l/hTank120LFuelDieselRunning time200 HrGalvanized mast height8.5 mLifting systemHydraulicRotation350 °Wind resistance110 km/hTrailerRoad -towed trailerTyres185/70R13BasementBunded base 120%Stabilizers4 + 1CanopyPowder coating paintOptionalGrid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting headOptional not included:Weekly timer Hydraulic stabilizersShipmentWeekly timer Hydraulic stabilizersShipment10Truck10	Control unit	Deep Sea L401 MKII
Coolant Liquid Cylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy +/- 5% Auxiliary power 1.2kVA Fuel Consumption 0,60 I/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road - towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Unession 235x147x240 cm Weight 900 kg Truck 10	Engine	Yanmar 3TNV68
Cylinders 3 Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy +/- 5% Auxiliary power 1.2kVA Fuel Consumption 0,60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Speed	1500 rpm
Emissions Stage V Alternator Linz Alumen Rated outlet 3.5kVA Regulation Brushless Voltage accurancy +/-5% Auxiliary power 1.2kVA Fuel Consumption 0,60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Coolant	Liquid
Alternator Rated outlet Rated outlet Regulation Brushless Voltage accurancy +/- 5% Auxiliary power 1.2kVA Fuel Consumption 0,601/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road - towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Ueight Pook grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head	,	
Rated outlet Regulation Brushless Voltage accurancy 4/- 5% Auxiliary power 1.2kVA Fuel Consumption O,60 V/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road - towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10		
Regulation Brushless Voltage accurancy +/- 5% Auxiliary power 1.2kVA Fuel Consumption 0.60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road - towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 120L		
Voltage accurancy +/- 5% Auxiliary power 1.2kVA Fuel Consumption 0,60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AM/OSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 100	Rated outlet	3.5kVA
Auxiliary power 1.2kVA Fuel Consumption 0,60 l/h Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road-towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 100	Regulation	Brushless
Fuel Consumption0,60 l/hTank120LFuelDieselRunning time200 HrGalvanized mast height8.5 mLifting systemHydraulicRotation350°Wind resistance110 km/hTrailerRoad -towed trailerTyres185/70R13BasementBunded base 120%Stabilizers4 + 1CanopyPowder coating paintOptionalGrid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tillting headOptional not included:Weekly timer Hydraulic stabilizersShipmentWeightDimension235x147x240 cmWeight900 kgTruck10	Voltage accurancy	+/- 5%
Tank 120L Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Auxiliary power	1.2kVA
Fuel Diesel Running time 200 Hr Galvanized mast height 8.5 m Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road - towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Fuel Consumption	0,60 l/h
Running time Galvanized mast height Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck	Tank	120L
Galvanized mast height Lifting system Hydraulic Rotation 350 ° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Fuel	Diesel
Galvanized mast height8.5 mLifting systemHydraulicRotation350 °Wind resistance110 km/hTrailerRoad-towed trailerTyres185/70R13BasementBunded base 120%Stabilizers4 + 1CanopyPowder coating paintOptionalGrid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting headOptional not included:Weekly timer Hydraulic stabilizersShipment235x147x240 cmWeight900 kgTruck10	Running time	200 Hr
Rotation 350 ° Wind resistance 110 km/h Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 100	Galvanized mast height	8.5 m
Wind resistance Trailer Road -towed trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension Weight 900 kg Truck 110 km/h Road -towed trailer Road -towed tr	Lifting system	Hydraulic
Trailer Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional included: Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Rotation	350°
Tyres 185/70R13 Basement Bunded base 120% Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Wind resistance	110 km/h
Basement Stabilizers 4+1 Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional included as standard: Optional included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Trailer	Road -towed trailer
Stabilizers 4 + 1 Canopy Powder coating paint Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Tyres	185/70R13
Canopy Powder coating paint Optional Optional included as standard: Optional included as standard: Optional included: Optional not included: Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Basement	Bunded base 120%
Optional Optional included as standard: Grid/engine selector Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Stabilizers	4 + 1
Optional included as standard: Optional included as standard: Optional not included: Optional not included: Shipment Dimension Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Canopy	Powder coating paint
Daylight sensor with Autostart AMOSS kit Battery isolator Electric tilting head Optional not included: Weekly timer Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Optional	
Hydraulic stabilizers Shipment Dimension 235x147x240 cm Weight 900 kg Truck 10	Optional included as standard:	Daylight sensor with Autostart AMOSS kit Battery isolator
Dimension 235x147x240 cm Weight 900 kg Truck 10	Optional not included:	
Weight 900 kg Truck 10	Shipment	
Truck 10	Dimension	235x147x240 cm
	Weight	900 kg
Container 40"HC 10	Truck	10
	Container 40"HC	10

EnviroLED

Lighting Area (see MultiLed head on front page)

