



# DCA-300



### Why Blue Diamond and Denyo Generators?

Denyo Generators are widely regarded as the most bullet proof generators in the world.

This fact, combined with Blue Diamonds huge stock levels, ability to service nationally and legendary support makes it a winning combination.

### Super Silent Technology

The frame and housing are built with high strength materials, and all doors are engineered to minimise vibration. Sound Attenuated Enclosure is lined with special vibration-absorbent polymer material to reduce vibrations. This oil resistant material is bonded to the walls of the canopy with resilient adhesive that enhances its performance. The unit's airflow has been engineered to provide proper cooling at an absolute minimum noise level.

### Control Panel

No complicated Electronics! Simple Analogue Dials are easier to operate and create fewer faults than sets controlled by Electronics, especially in very hot and dusty environments. Warning Lights and analogue gauges (including fuel, tachometer, oil pressure, coolant temperature and charging system amps) providing easy monitoring of engine operations.

### Compact Design

These Japanese engineered sets are generally more compact than other generators. This makes them far more versatile and portable.

### More Efficient

By only using the best Japanese engines available, such as Kubota and Isuzu, our generators will use less fuel than other machines on the market. In Prime power applications this can mean massive savings for the end user over the period of the project.

### Mine Site or Rental Options

Blue Diamond can customize your Denyo Generator to suit any application

### Denyo features below are optional extras:

- Heavy Duty Skid with Fork Points
- Power Outlets
- Lockable Battery Isolator
- Fire Extinguisher
- Long Rang Fuel Tank
- 3 Way Fuel Valve
- Hi Vis Tape



Mine site ready and compliant



### DIESEL GENERATOR – DCA-300

Continuous Output	270/300KVA
Frequency/Standby Rating	50 Hz
Voltage	415V
Power Factor	Three Phase 0.8
Output Rating PS/rpm	316/1500
Excitation	Brushless, Rotating Exciter
No. of Phase	3-Phase 0.8
Engine Make And Model	Komatsu SA6D125E-2-A
No. of Cylinders	6-125x150
Type	Inlined, Direct Injected, Turbocharged, Aftercooled
Piston Displacement	11.040
Rated Output kW/rpm	232/1500
Fuel	Diesel
Fuel Tank Capacity	490L
Fuel Consumption (75% Load)	43.6 L/Hr
Lubricating Oil Capacity	62L
Cooling Water Capacity	35L
Battery	145G51x2 or 155G51x2
Overall Length	3750mm
Overall Width	1400mm
Overall Height	1800mm
Net Dry Mass	4160kg



## Efficient. Reliable. Bullet Proof.

1300 998 647 | [info@bluedm.com.au](mailto:info@bluedm.com.au) | [bluedm.com.au](http://bluedm.com.au)