



FEATURES

- 50°C temperature rating
- ComApL-9controller
- Enclosed Silenced Canopy
- Powder coated finish
- Fork Points and centre liftinglug
- ABB Breakers
- 110% double bunded base
- Emergency E stop
- Australian Compliant Wiring and M.E.N link
- Remote Start and ATSfeature
- Site safe lockable canopy
- Pricing includes commissioning and pre delivery run in

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010

OPTIONAL UPGRADES

Fire extinguisher
battery & starter Isolator
Solar battery charger
3-way fuel valve
ComAp cell phone monitoring

WARRANTY

2 year – 1000 hour

Prime power (prp) Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T 2820-97 eqv ISO 8528; a 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby power rating (esp) The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

GEN 100YT

Silent Diesel Generator



ENGINE DATA

Make & Model	YTO LR4M3L-D60EF	
Type	Water Cooled, Turbo/Intercooler Engine	
Output Rating	Ps/Rpm	107/1500
	Kw/Min	80/1500
Bore X Stroke	Mm	110X 125mm
Position Displacement	L	4.75
Fuel Type	Diesel	
Fuel Consumption (Based On 75% Full Load)	L/H	11.5
Lube Oil Pump Capacity	L	14
Coolant Capacity	L	6(Engine only)
Battery X Quantity	2 X 60Ah	
Fuel Tank Capacity	L	540

ALTERNATOR DATA

Alternator	Dingol DG274C	
Frequency	(Hz)	50
Output Rating	Continuous (KVA)	90
	Standby (KVA)	100
No. of Phase	3 Phase, 4 Wire	
Rated Voltage	V	240/415
Power Factor	0.8 (Lagging)	
Voltage Regulation	%	+1
Excitation	Self Exciting	
Insulation	Class H	

SOUND

Sound Level	7m dB(A)	64
-------------	----------	----

DIMENSIONS

Dimensions	Length (mm)	2900
	Width (mm)	1130
	Height (mm)	1800
Dry weight	Kg	2000